

TITLE OF THE INVENTION

ROUTE OPTIMIZATION METHOD AND AGENT APPARATUS

BACKGROUND OF THE INVENTION

## 5 1. Field of the Invention

The present invention generally relates to a route optimization method and an agent apparatus and, more particularly, to a route optimization method and an agent apparatus by which  
10 an IP packet route is optimized in a communication system employing the Mobile IP protocol.

## 2. Description of the Related Art

Mobile IP, proposed by Internet Engineering Task Force (IETF), is known as a method  
15 for a mobile terminal having an IP address to maintain communication without terminating a session even when the mobile terminal moves across network domains.

Fig. 30 shows how a packet is  
20 transmitted according to the Mobile IP protocol of the related art.

Referring to Fig. 30, the mobile terminal 11 has a permanent IP address in a home domain (hereinafter, simply referred to as a home  
25 address). A home agent (HA) 13 is located in the home domain to which the mobile terminal 11 belongs. Numeral 41 indicates a correspondent terminal with which the mobile terminal 11 communicates. The correspondent terminal 41 may be a land unit or a  
30 mobile unit. An abbreviation CN/MT (correspondent

T06250"4695986

node/mobile terminal) will also be used to denote the correspondent terminal 41. Numeral 201 indicates a foreign agent (FA) located in a destination domain of the mobile terminal 11 and has a care-of address.

A description will now be given of how a packet is transmitted according to Mobile IP.

After moving to a destination domain, the mobile terminal 11 acquires an address assigned to itself in the destination domain in the form of a care-of address. The mobile terminal 11 notifies the home agent 13 of the care-of address via the foreign agent 201. The home agent 13 registers the care-of address from the mobile terminal 11 in relation to the home address of the mobile terminal 11.

The correspondent terminal 41, requesting an IP packet to be sent to the mobile terminal 11, sends an IP packet destined for the home address of the mobile terminal 11. The IP packet arrives at the home agent 13 via an IP network 220. The home agent 13 encapsulates the IP packet based on information registered for the mobile terminal 11 and then forwards the encapsulated packet to the care-of address of the mobile terminal 11. The foreign agent 201 receiving the encapsulated IP packet decapsulates the packet and delivers the original IP packet to the mobile terminal 11 having the care-of address.

When the mobile terminal 11 is located

in the home domain, the home agent 13 operates as a router so that the IP packet addressed to the mobile terminal 11 is routed to the mobile terminal 11.

5                   Thus, even when the mobile terminal 11 moves across domains, the IP packet addressed to the mobile terminal 11 is ensured to arrive at the mobile terminal 11 via the home agent 13 and the foreign agent 201.

10                   One problem with the base Mobile IP protocol is that, when the IP packet addressed to the mobile terminal 11 arrives at the mobile terminal 11 via the home agent 13, a packet may follow a path which is longer than an optimal path. x  
15 When this triangular routing occurs, a relatively large transmission delay may be incurred. The transmission delay presents a serious problem when the data transmission is concerned with voice over IP datagrams, which are relatively less tolerant of  
20 delay.

                  An internet draft from the IETF (draft-ietf-mobileip-optim-08.txt) proposes Route Optimization to resolve the problem of transmission delay caused by triangular routing. Route  
25 Optimization uses a protocol for establishing a shortcut path from the correspondent terminal to the care-of address of the mobile terminal 11, y  
bypassing the home agent 13. Fig. 31 shows Route Optimization applied to the related-art Mobile IP.

30                   In the proposed Route Optimization, the

09865694.052901

Thus, as shown in Fig. 31, the IP packet from the correspondent terminal 41 addressed to the mobile terminal 11 arrives at the mobile terminal 11, bypassing the home agent 13. This way, the problem with triangular routing is resolved.

25                   In the related-art Route Optimization,  
the size of a header portion of the IP packet  
doubles due to encapsulation, thus preventing the  
bandwidth for transmission from the correspondent  
terminal 41 to the foreign agent or the home agent  
30 of the domain to which the correspondent terminal

41 belongs from being effectively used.  
Particularly, VoIP packets presents a serious  
problem since the size of a header portion is  
relatively large in relation to the data portion.

5

#### SUMMARY OF THE INVENTION

Accordingly, an object of the present  
invention is to provide a route optimization method  
and an agent apparatus in which the aforementioned  
10 problems are eliminated.

Another and more specific object is to  
provide a route optimization method and an agent  
apparatus in which the Binding Update Message from  
the home agent is received by a home agent or a  
15 foreign agent to which the correspondent terminal  
41 is attached and the home agent or the foreign  
agent encapsulates a packet destined for the mobile  
terminal 11 for transmission thereto, thereby  
x eliminating the need for periodical message  
20 exchange between the correspondent terminal 41 and  
the home agent 13 for the mobile terminal 11,  
reducing the power consumption of the correspondent  
terminal 41, and effectively using the transmission  
bandwidth by reducing the volume of data  
25 transmitted from the correspondent terminal 41 to  
the foreign agent of the domain to which the  
correspondent terminal 41 belongs.

The aforementioned objects can be  
achieved by a route optimization method for a  
30 communication system that allows communication

09865694-052901

between a mobile terminal and a correspondent terminal, for optimizing a route for communication between the correspondent terminal and the mobile terminal when the mobile terminal moves across network domains, comprising the steps of: causing a foreign agent or a home agent of a network domain to which the correspondent terminal currently belongs to receive a Binding Update Message from a home agent for the mobile terminal and to forward a packet destined for the mobile terminal to a care-of address of the mobile terminal specified in the Binding Update Message.

The route optimization method may further comprise the steps of: causing the foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs to repeat transmission of a Binding Request Message to the home agent for the mobile terminal in order to acquire the latest care-of address; and causing the home agent for the mobile terminal to transmit, in response to the Binding Request Message, a Binding Acknowledge Message containing the latest care-of address of the mobile terminal to the foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs.

The route optimization method may further comprise the steps of: causing the foreign agent or the home agent of the network domain to which the correspondent terminal belongs to combine

09365694-052901

The foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may use subnet masking to maintain a list of home agents capable of interpreting an extended Binding Request Message, so as to send the extended Binding Request Message for the plurality of mobile terminals to the home agent capable of interpretation and send the Binding Request Message for each mobile terminal to the other home agents.

The home agent for the mobile terminal may notify the foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs whether the home agent is capable of interpreting the extended Binding Request Message, and the foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may dynamically determine whether the home agent for the mobile terminal is capable of interpreting the extended Binding Request Message, based on the notification, so that the foreign agent or the home agent sends the extended Binding Request Message for the plurality of mobile terminals to the home

agent capable of interpreting the extended Binding Request Message and sends the Binding Request Message for each mobile terminal to the home agent.

5 The foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may accept only the Binding Update Message from the selected home agents.

10 The foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may use a subnet mask to maintain a list of home agents originating the acceptable Binding Update Message.

15 The foreign agent or the home agent may forward only the packet from the selected correspondent terminals to the mobile terminal.

20 The foreign agent or the home agent may use a subnet mask to designate a group of correspondent terminals with respect to route optimization.

25 The foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may control an interval of transmission of the Binding Request Message in accordance with a frequency of change of the care-of address.

30 The foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may set an initial value of priority of update for each mobile terminal,

0965594-05290  
T06250-46959860



compute the priority of update in accordance with the frequency of change of the care-of address, and set the interval of transmission of the Binding Request Message in accordance with the priority of  
5 update.

The foreign agent or the home agent of the network domain to which the correspondent terminal currently belongs may maintain a plurality of care-of addresses for the mobile terminal and  
10 forward the packet destined to a home address of the mobile terminal to each of the plurality of care-of addresses.

The foreign agent or the home agent of the network domain visited by the correspondent  
15 terminal may acquire the care-of address of the mobile terminal from the foreign agent or the home agent of the network domain from which the visiting correspondent terminal arrives.

The foreign agent or the home agent of  
20 the network domain to which the correspondent terminal currently belongs may monitor a volume of packets destined for the mobile terminal or packets from the mobile terminal so as to control update of the care-of address of the mobile terminal in  
25 accordance with the monitored volume.

The foreign agent or the home agent may suspend update of the care-of address when the correspondent terminal moves out of the network domain.

30 The foreign agent or the home agent may

0985594.052901  
T06250"46959860

resume the suspended update of the care-of address when a predetermined condition is met.

The aforementioned objects can also be achieved by an agent apparatus for a communication system in which a mobile terminal communicates with a correspondent terminal, operated as a foreign agent or a home agent for a network domain to which the correspondent terminal belongs, comprising: receiver for receiving a Binding Update Message from a home agent for the mobile terminal; and transmitter for forwarding a packet destined for the mobile terminal to a current care-of address of the mobile terminal designated in the Binding Update Message.

15

#### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and further features of the present invention will be apparent from the following detailed description when read in conjunction with the accompanying drawings, in which:

20

Fig. 1 shows an example of a network to which route optimization according to a first embodiment is applied;

25

Fig. 2 is an SDL diagram showing an operation of a foreign agent;

Fig. 3 shows an example of an attached terminal management table provided in the foreign agent with which a mobile terminal is connected;

30

Fig. 4 shows an example of a binding

09865694-052904  
F06250-46959860

cache table provided in the foreign agent with which a correspondent terminal is connected;

Fig. 5 is an SDL diagram showing an operation of the correspondent terminal;

5 Fig. 6 is an SDL diagram showing an operation of the mobile terminal;

Fig. 7 is an SDL diagram showing an operation of a home agent;

10 Fig. 8 shows an example of a care-of address management table provided in the home agent for the mobile terminal;

Fig. 9 shows a sequence of care-of address registration and packet transmission;

15 Fig. 10 shows an example of a network to which the route optimization according to a third embodiment is applied;

Fig. 11 shows an example of an extended Binding Request Message according to the third embodiment;

20 Fig. 12 shows an example of a HA support table;

Fig. 13 is an SDL diagram showing an operation performed when the home agent capable of interpreting the extended Binding Request Message  
25 receives the Binding Request Message;

Fig. 14 shows an example of a HA support table in which a subnet mask is introduced;

Fig. 15 shows an example of a Binding Update Message used when the HA support table is  
30 dynamically set;

09865694.052901

Fig. 16 shows an example of an internal table in which selected home agents are registered;

Fig. 17 shows an example of an internal table in which grouping using a subnet mask is  
5 introduced;

Fig. 18 shows an example of a service setting table;

Fig. 19 is an SDL diagram showing an operation of a foreign agent according to an eighth  
10 embodiment receiving an IP packet;

Fig. 20 shows an example service setting table in which a subnet mask is introduced;

Fig. 21 is an SDL diagram showing an operation for adjusting an interval of transmission  
15 of a Binding Request Message from the foreign agent;

Fig. 22 shows a binding cache table of the foreign agent according to the tenth  
embodiment;

Fig. 23 shows an example of a service setting table provided in the foreign agent  
20 according to an eleventh embodiment;

Fig. 24 shows an example of an extended Binding Update Message according to a twelfth  
25 embodiment;

Fig. 25 shows that the correspondent terminal of the network shown in Fig. 1 moves to a remote IP network;

Fig. 26 is an SDL diagram showing an  
30 operation of the foreign agent according to a

0965694.052901  
T06250"4695980

thirteenth embodiment;

Fig. 27 is an SDL diagram showing an operation of the foreign agent according to the thirteenth embodiment;

5 Fig. 28 shows a sequence of operations performed by terminals and agents when the correspondent terminal moves to a remote IP network;

Fig. 29 shows an example of an extended  
10 Binding Acknowledge Message according to the thirteenth embodiment;

Fig. 30 shows how a packet is transmitted according to the Mobile IP protocol of the related art; and

15 Fig. 31 shows Route Optimization applied to the related-art Mobile IP.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

##### First embodiment

20 Fig. 1 shows an example of a network to which the route optimization according to a first embodiment is applied.

Referring to Fig. 1, an IP network (network domain) 1 is a home domain for a mobile  
25 terminal 11. An IP network (network domain) 3 is a destination domain of the mobile terminal 11. An IP network (network domain) 4 is a home domain for a correspondent terminal 41. An IP network (network domain) 5 is a destination domain of the  
30 correspondent terminal 41. Numeral 6 indicates an

09065694.052901

additional IP network (network domain). The Internet 2 connects the IP networks 1, 3-6 to each other.

The mobile terminal 11 has a permanent IP address in the home domain (home address). A base station 12 is connected to the home agent 13 so as to communicate with mobile terminals located in the IP network 1. A home agent (agent apparatus) 13 is located in the home domain to which the mobile terminal 11 belongs. In the illustrated example, the network address of the IP network 1 is 10.75.51.0, the home address of the mobile terminal 11 is 10.76.51.100 and the IP address of the home agent 13 is 10.76.51.254.

A base station 31 is connected to the foreign agent 32 and communicates with the mobile terminal 11 located in the IP network 3 and with the correspondent terminal 41 over a radio channel. A foreign agent (agent apparatus) 32 is located in the IP network 3. The network address of the IP network 3 is 10.76.52.0 and the IP address of the foreign agent 32 is 10.76.52.254.

The correspondent terminal 41 communicates with the mobile terminal 11. The correspondent terminal 41 may be a land unit or a mobile unit. A base station 42 is connected to a home agent 43 and communicates with terminals located in the IP network 4 over a radio channel. The home agent (agent apparatus) 43 is located in the home domain to which the correspondent terminal

09065694-052904

41 belongs. The network address of the IP network 4 is 10.76.55.0, the home address of the correspondence terminal 41 is 10.76.55.100 and the IP address of the home agent 43 is 10.76.55.254.

5           A base station 51 is connected to a foreign agent 52 and communicates with terminals located in the IP network 5. The foreign agent (agent apparatus) 52 is located in the IP network 5. The network address of the IP network 5 is  
10 10.76.53.0 and the IP address of the foreign agent 52 is 10.76.53.254.

          A base station 61 is connected to a foreign agent 62 and communicates with terminals located in the IP network 6. The foreign agent  
15 (agent apparatus) 62 is located in the IP network 6 and has a care-of address. The network address of the IP network 6 is 10.76.54.0 and the IP address of the foreign agent 62 is 10.76.54.254.

          The home agent 13, the mobile terminal  
20 11 and the correspondent terminal 41 operate as entities that comply with the Mobile IP specification.

          A description will now be given of the operation of the terminals and agents.

25           First, the operation of the foreign agents 32, 52 and 62 will be described. Fig. 2 is a specification and description language (SDL) diagram showing the operation of the foreign agents 32, 52 and 62. Figs. 3 shows an example of an  
30 attached terminal management table provided in the

09865694 052901  
T06220 46959860

foreign agent (32, 52, 62) attached to the mobile terminal 11. Fig. 4 shows an example of a bidding cache table provided in the foreign agent (32, 52, 62) attached to the correspondent terminal 41.

5                   When the mobile terminal 11 moves to the IP network (3, 5, 6), the mobile terminal 11 transmits a Registration Request Message destined for the home agent 13 to the foreign agent (32, 52, 62) of the destination IP network (3, 5, 6) via the  
10 base station (31, 51, 61). The Registration Request Message includes the home address of the mobile terminal 11, the address of the home agent 13 and the care-of address acquired in the IP network (3, 5, 6).

15                   In step ST11, the foreign agent (32, 52, 62) receives the Registration Request Message from the mobile terminal 11 located in the home IP network (3, 5, 6) via the base station (31, 51, 61). In step ST12, the foreign agent (32, 52, 62)  
20 searches the attached terminal management table as shown in Fig. 3. In step ST13, the foreign agent (32, 52, 62) makes a determination as to whether the mobile terminal 11 is registered in the attached terminal management table. If it is  
25 determined that the mobile terminal 11 is registered in the attached terminal management table, registered information is updated bases on the Registration Request Message in step ST14. If  
30 it is determined that the mobile terminal 11 is not registered in the attached terminal management

09065694-052901  
T06250-46959860



table, the foreign agent (32, 52, 62) registers the mobile terminal 11 in the attached terminal management table in step ST15 based on the Registration Request Message.

5                   In step ST16, the foreign agent (32, 52, 62) forwards the Registration Request Message to the home agent 13 for the mobile terminal 11.

                  In step ST21, the foreign agent (32, 52, 62) receiving an IP packet from a terminal in the  
10 Internet 2 or the home IP network (3, 5, 6) examines the header portion of the IP packet so as to determine whether the IP packet is destined for an IP address in the home IP network (3, 5, 6). If is determined that the IP packet is destined for an  
15 IP address in the home IP network (3, 5, 6), the foreign agent (32, 52, 62) decapsulates the IP packet in step ST23 and delivers the original IP packet to a corresponding terminal in the home IP network (3, 5, 6) in step ST24. *✓ end*

20                   When it is determined that the IP packet is not destined for an IP address in the home IP network (3, 5, 6), the foreign agent (32, 52, 62) searches the binding cache table as shown in Fig. 4 *✓* (described later) in step ST25. In step ST26, the  
25 foreign agent (32, 52, 62) determines whether the mobile terminal 11, to which the IP packet is addressed, is registered in the binding cache table. If it is determined that the mobile terminal 11 is registered in the binding cache table, the foreign  
30 agent (32, 52, 62) reads the care-of address for

09865694.052901  
106250 16959860

the mobile terminal 11 from the binding cache table in step ST27. The foreign agent (32, 52, 62) then encapsulates the IP packet and forwards, in step ST28, the encapsulated IP packet to the care-of address of the mobile terminal 11 to which the original IP packet is addressed. If it is determined that the mobile terminal 11 is not registered in the binding cache table, the foreign agent (32, 52, 62) forwards the IP packet in step ST28 without encapsulation.

In step ST31, the foreign agent (32, 52, 62) receives a Binding Update Message from the home agent 13 for the mobile terminal 11. In step ST 32, the foreign agent (32, 52, 62) searches the binding cache table as shown in Fig. 4. In step ST33, the foreign agent (32, 52, 62) determines whether the mobile terminal 11, specified in the Binding Update Message, is registered in the binding cache table. If it is determined that the mobile terminal 11, specified in the Binding Update Message, is registered in the binding cache table, the foreign agent (32, 52, 62) updates registered information in step ST34 based on the Binding Update Message. If it is determined that the mobile terminal, specified in the Binding Update Message, is not registered in the binding cache table, the foreign agent (32, 52, 62) registers the mobile terminal 11 in the binding cache table in step ST35 based on the Binding Update Message. The Binding Update Message includes the home address of the mobile

09065694.052901

terminal 11, the care-of address thereof, the address of the home agent and a timeout value of the Message. The binding cache table also includes similar information registered therein.

5           A description will now be given of the operation of the correspondent terminal 41. Fig. 5 is an SDL diagram showing the operation of the correspondent terminal 41. In step ST41, the correspondent terminal 41 receives the IP packet  
10 via the foreign agent (32, 52, 62) or the home agent 43. The foreign agent (32, 52, 62) or the home agent 43 is responsible for encapsulation and decapsulation so that the correspondent terminal 41 according to the first embodiment does not have to  
15 handle encapsulation and decapsulation.

          A description will now be given of the operation of the mobile terminal 11. Fig. 6 is an SDL diagram showing the operation of the mobile terminal 11. In step ST51, the mobile terminal 11  
20 receives a Registration Acknowledge Message from the home agent 13 in response to a Registration Request Message. In step ST61, the mobile terminal 11 receives an agent advertisement from the foreign agent (32, 52, 62) of the IP network (3, 5, 6) in  
25 which the mobile terminal 11 is located. In step ST62, the mobile terminal 11 acquires a care-of address corresponding to the agent advertisement. In step ST63, the mobile terminal 11 generates a Registration Request Message that includes the  
30 care-of address of the mobile terminal 11 and

T06250" 46959860

transmits the Registration Request Message to the home agent 13 via the foreign agent (32, 52, 62). In step ST71, the mobile terminal 11 receives the IP packet via the foreign agent (32, 52, 62) or the home agent 13.

Fig. 7 is an SDL diagram showing the operation of the home agent 13. Fig. 8 shows an example of a care-of address management table for the mobile terminal 11 provided in the home agent 13.

Upon receipt of the Registration Request Message from the mobile terminal 11 in step ST81, the home agent 13 for the mobile terminal 11 searches the care-of address management table as shown in Fig. 8 in step ST82. In step ST83, the home agent 13 determines whether the mobile terminal 11 is registered in the care-of address management table. If it is determined that the mobile terminal 11 is registered in the care-of address management table, the home agent 13 updates information registered in the table based on the Registration Request Message in step ST84. If it is determined that the mobile terminal 11 is not registered in the care-of address management table, the home agent 13 registers the mobile terminal 11 in the care-of address management table based on the Registration Request Message in step ST85.

In step ST86, the home agent 13 transmits a Registration Acknowledge Message to the mobile terminal 11 indicating that registration is

09855694-052901  
T06250-1695960

complete.

Upon receipt of an IP packet from a terminal in the Internet 2 or the home IP network (3, 5, 6) in step ST91, the home agent 13 searches the care-of address management table in step ST92. In step ST93, the home agent 13 determines whether the mobile terminal 11, to which the IP packet is addressed, is registered in the care-of address table.

10 If it is determined that the mobile terminal 11, to which the IP packet is addressed, is registered in the care-of address management table, the home agent 13 reads the care-of address of the mobile terminal 11 from the care-of address in step ST94 so as to encapsulate the IP packet. In 15 step ST95, the home agent 13 transmits a Binding Update Message for the mobile terminal 11, to which the IP packet is addressed, to a sender of that IP packet. In step ST96, the home agent 13 forwards 20 the encapsulated IP packet to the mobile terminal 11. If it is determined in step ST93 that the mobile terminal 11 is not registered in the care-of address management table, the home agent 13 determines that the mobile terminal 11 is located 25 in the home domain. In step ST96, the home agent 13 delivers the IP packet to the mobile terminal 11 via the base station 12.

When receiving in step ST101 a Binding Request Message for the mobile terminal 11 from the 30 foreign agent (32, 52, 62) of the domain to which

052904-46959850

the correspondent terminal 41 currently belongs, the home agent 13 searches the care-of address management table as shown in Fig. 8 in step ST102..

In step ST103, the home agent 13 transmits a

- 5 Binding Update Message for mobile terminal 11 to the contacting foreign agent (32, 52, 62).

The home agent 43 may also be configured to perform a similar operation with respect to the correspondent terminal 41.

- 10 A description will now be given of how a care-of address of the mobile terminal 11 is registered in the home agent 13 when the mobile terminal 11 moves from the IP network 1 to the IP network 3, and how the correspondent terminal 41
- 15 sends a packet to the mobile terminal 11. Fig. 9 shows a sequence of registration of the care-of address of the mobile terminal 11 and packet transmission. The base stations 12, 31, 42, 51 and 61 only perform transparent transmission so that
- 20 the operation thereof is omitted. Since the correspondent terminal 41 remains stationary, it may be considered as a land unit.

- A description will now be given of how the care-of address of the mobile terminal 11 is
- 25 registered in the home agent 13 when the mobile terminal 11 has moved from the IP network 1 to the IP network 3.

- When the mobile terminal 11 has moved from the IP network 1 to the IP network 3, the
- 30 mobile terminal 11 acquires the care-of address

through the Dynamic Host Configuration Protocol (DHCP). The mobile terminal 11 registers the care-of address in the foreign agent 32 and the home agent 13 by transmitting a Registration Request  
5 Message to the foreign agent 32. The Registration Request Message includes the care-of address of the mobile terminal 11, the home address of the mobile terminal 11, the address of the home agent 13 for the mobile terminal 11.

10 The foreign agent 32 receiving the Registration Request Message determines that the mobile terminal 11 is visiting the home IP network 3. The foreign agent updates the attached terminal management table so that the home address  
15 10.76.51.100 of the mobile terminal 11 is mapped into the address 10.76.51.254 of the home agent 13.

Further, the foreign agent 32 forwards the Registration Request Message to the home agent 13 so that the new care-of address of the mobile  
20 terminal 11 is registered in the home agent 13 for the mobile terminal 11.

Upon receipt of the Registration Request Message, the home agent 13 updates the care-of address management table shown in Fig. 8 so that  
25 the care-of address 10.76.52.254 included in the Registration Request Message is mapped into the home address 10.76.51.100 of the mobile terminal 11.

Before moving to the IP network 3, the mobile terminal 11 was accommodated in the home IP  
30 network 1 so that the mobile terminal 11 did not

09865694-052901  
T06250-16959860

have a care-of address. Correspondence between the home address of the mobile terminal 11 and the care-of address was not registered in the care-of address management table. Thus, when the mobile terminal 11 moves to the IP network 3, the care-of address 10.76.52.254 is delivered to the home agent 13 for the first time. The home agent 13 registers the care-of address of the mobile terminal 11 in the care-of address management table shown in Fig. 8 for the first time. The home agent 13 transmits a Registration Acknowledge Message to the sender of the Registration Request Message to indicate that the care-of address is registered for the first time in the care-of address management table or the care-of address management table is updated.

The foreign agent 32 receiving the Registration Acknowledge Message forwards it to the mobile terminal 11 in order to inform the mobile terminal 11 that registration is complete.

When the registration of the mobile terminal 11 in the home agent 13 is complete, the information relating to the mobile terminal 11 is registered as shown in Fig. 3 in the attached terminal management table of the foreign agent 32. The information relating to the mobile terminal 11 is also registered as shown in Fig. 8 in the care-of address management table of the home agent 13. The process of registration described above is in accordance with the specification of the Mobile IP protocol.

05865694-052901



A description will now be given of the routing between the correspondent terminal 41 and the mobile terminal 11.

The correspondent terminal 41 transmits  
5 an IP packet to the mobile terminal 11 without encapsulation. The IP packet is received by the foreign agent 52 of the IP network 5 to which the correspondent terminal 41 currently belongs. If the address of the IP packet (home address 10.76.51.100  
10 of the mobile terminal 11) is not identified in the binding cache table shown in Fig. 4, the foreign agent 52 transmits the IP packet transparently to the destination.

The home agent 13 receiving the IP  
15 packet encapsulates the IP packet based on the information registered for the mobile terminal 11 in the care-of address management table generated in the registration process. The home agent 13 then tunnels the encapsulated packet to the care-of  
20 address 10.76.52.254.

The IP packet tunneled by the home agent 13 arrives at the foreign agent 32. The packet is decapsulated by the foreign agent 32 so that the original IP packet arrives at the mobile terminal  
25 11.

The packet follows a path according to the triangular routing since the binding cache table of the foreign agent 52 does not include information registered for the mobile terminal 11.

30 When tunneling the IP packet, the home

09865694-052901

agent 13 sends a Binding Update Message to the correspondent terminal 41. The foreign agent 52 receives the Binding Update Message so as to register the information relating to the mobile terminal 11 in the binding cache table as shown in Fig. 4. Since the corresponding terminal 41 is not supplied with the Binding Update Message, it continues to send packets to the home address 10.76.51.100 of the mobile terminal 11 without encapsulation.

After the information relating to the mobile terminal 11 is registered in the binding cache table of the foreign agent 52, the foreign agent 52 encapsulates IP packets from the correspondent terminal 41 based on the information registered in the binding cache table for the mobile terminal 11. The foreign agent 52 tunnels the encapsulated packet to the care-of address 10.76.52.254 of the mobile terminal 11. More specifically, the foreign agent 52 reads the destination IP address 10.76.51.100 from the header portion of the IP packet from the correspondent terminal 41 and searches for the registered information bound to the home address identical to the destination IP address. The foreign agent 52 determines that the care-of address 10.76.52.254 bound to the registered information is the care-of address of the mobile terminal 11.

Thus, the encapsulated IP packet arrives at the foreign agent 32, bypassing the home agent

0965594-052904  
T06250-16959360

13. In this way, the disadvantage with triangular routing is resolved.

As described, according to the first embodiment, the Binding Update Message from the home agent 13 is received by the foreign agent (32, 52, 62) to which the correspondent terminal 41 is attached so that the foreign agent (32, 52, 62) encapsulates the IP packet addressed to the mobile terminal 11 before transmission. Accordingly, the need for periodical communication between the correspondent terminal 41 and the home agent 13 for the mobile terminal 11 is eliminated, thus reducing the power consumption of the correspondent terminal 41. Moreover, the transmission bandwidth is efficiently used by reducing the volume of data transmitted from the correspondent terminal 41 to the foreign agent 52 of the domain to which the correspondent terminal 41 belongs.

## 20 Second embodiment

The foreign agent (32, 52, 62) according to a second embodiment transmits a Binding Request Message to the home agent 13 before the expiration of lifetime specified in the Binding Update Message, in order to prompt the home agent 13 for transmission of a Binding Update Message. The Binding Request Message complies with the Internet draft (draft-ietf-mobileip-optim-08.txt). In this case, the Binding Request Message includes the home address of the mobile terminal 11.

09655694-052904

The home agent 13 receiving the Binding Request Message returns the Binding Update Message including the latest care-of address corresponding to the home address of the mobile terminal 11 to the sender of the Binding Request Message. The foreign agent (32, 52, 62) receiving the Binding Update Message updates the care-of address of the mobile terminal 11 in the binding cache table based on the Binding Update Message.

The other aspects of the second embodiment are the same as the corresponding aspects according to the first embodiment so that the description thereof is omitted.

As described, according to the second embodiment, it is ensured that the foreign agent (32, 52, 62) of the domain to which the correspondent terminal 41 belongs periodically sends a message to the home agent 13 in order to acquire the latest care-of address of the mobile terminal 11. Thereby, route optimization is achieved without the periodical communication between the correspondent terminal 41 and the home agent 13. With this, packets are tunneled to the latest care-of address. Moreover, the volume of data transmitted from the correspondent terminal 41 to the foreign agent (32, 52, 62) of the domain to which the correspondent terminal 41 belongs is reduced.

30 Third embodiment

Fig. 10 shows an example of a network to which the route optimization method according to a third embodiment is applied. Referring to Fig. 10, the IP network 1 is the home domain for mobile terminals 11-1 and 11-2. The mobile terminals 11-1 and 11-2 communicate with correspondent terminals 41-1 and 41-2, respectively. The IP network 4 is the home domain for the correspondent terminals 41-1 and 41-2. The home address of the correspondent terminal 41-1 is 10.76.55.100 and the home address of the mobile terminal 11-1 which communicates with the correspondent terminal 41-1 is 10.76.51.100. The home address of the correspondent terminal 41-2 is 10.76.55.101 and the home address of the mobile terminal 11-2 which communicates with the correspondent terminal 41-2 is 10.76.51.101.

As indicated in Fig. 10, the foreign agent 52 (32, 62) according to the third embodiment combines a plurality of Binding Request Messages, requesting the current mobility binding of the mobile terminals 11-1 and 11-2, into an extended Binding Request Message, when the corresponding terminals 41-1, 41-2 located in the home IP network 5 (3, 6) respectively communicate with the mobile terminals 11-1 and 11-2 that belong to the same home domain. The foreign agent 52 (32, 62) transmits the extended Binding Request Message to the home agent 13.

The foreign agent 52 (32, 62) according to the third embodiment is provided with a HA

support table in which home agents capable of interpreting an extended Binding Request Message are listed. The foreign agent 52 (32, 62) refers to the HA support table so as to send the extended

5 Binding Request Message to a home agent only when the home agent is capable of interpreting an extended Binding Request Message. Otherwise, the foreign agent 52, (32, 62) sends a normal (unextended) Binding Request Message.

10 Fig. 11 shows an example of an extended Binding Request Message according to the third embodiment. As shown in Fig. 11, in addition to the information included in the normal Binding Request Message, the extended Binding Request Message

15 includes an extension type 101, which is permanently set to "38", a length of the extension 102, a vendor identifier 103, which is a vendor-specific identifier, a vendor extension type 104, which is a vendor-specific extension type, and home

20 addresses 105 and 106 of the mobile terminals for which the Binding Update Message is requested.

The message extension described above is in conformity with the critical vendor extension format of the IETF Internet draft (draft-ietf-

25 vender-ext-05.txt). According to this draft, when the foreign agent not capable of interpreting the extension receives the message extended in accordance with the critical vendor extension format, the whole message is ignored. Accordingly,

30 when the home agent receives the extended Binding

0065694.052901  
T06250.46959860

Fig. 12 shows an example of a HA support table. As shown in Fig. 12, the table defines the mapping between the IP address of the home agent 13 for the mobile terminal and information indicating whether the home agent is capable of interpreting the extended Binding Request Message.

When the correspondent terminals 41-1 and 41-2 located in the home IP network 5 (3, 6) respectively communicate with the mobile terminals 11-1 and 11-2 having the same home domain, the foreign agent 52 (32, 62) according to the third embodiment sends the extended Binding Request Message to the home agent 13 capable of interpreting the extended Binding Request Message by referring to the HA support table. The foreign agent 52 (32, 62) sends the normal (unextended) Binding Request Message to the home agent 13 not having the interpreting capability.

In steps ST101-ST103, the home agent 13

according to the third embodiment reads, from the care-of address management table, the latest care-of address corresponding to the home address of the mobile terminal included in unextended portion of the received Binding Request Message. The home agent 13 then sends a Binding Update Message that includes the latest care-of address to the foreign agent 52 (32, 62) originating the Binding Request Message.

Subsequently, in step ST111, the home agent 13 determines whether the received Binding Request Message includes an extended portion. If it is determined that the Message does not contain an extended portion, the process is terminated. If it is determined that the Message contains an extended portion, control is turned to step ST12 where the home agent 13 reads, from the care-of address management table, the latest care-of addresses corresponding to the home addresses of the mobile terminals listed in the extended portion. In step ST113, the home agent 13 transmits the Binding Update Message that includes the latest care-of addresses to the sender of the Binding Request Message. The home agent 13 repeats the steps ST111-ST113 until the home addresses of the mobile terminals listed in the extended portion are exhausted.

The other aspects of the operation are the same as corresponding aspects according to the first embodiment so that the description thereof is

09065694-052901  
T06250-16959860





5

0

15

20

25

Fig. 15 shows an example of a Binding  
30 Update Message for dynamically setting the HA

5

10

15

30

the description thereof is omitted.

As described, according to the fifth embodiment, the foreign agent (32, 52, 62) is allowed to dynamically set a HA support table in accordance with a notification from the home agent 13. Accordingly, a network manager need not manually set the HA support table of the foreign agent (32, 52, 62). Indication as to whether the home agent 13 is capable of interpreting an extended Binding Request Message is automatically set in the HA support table. An advantage of the fifth embodiment is that the setting of the HA support table is simplified.

#### 15 Sixth embodiment

The foreign agent (32, 52, 62) according to a sixth embodiment accepts a Binding Update Message from the selected home agent 13.

Route Optimization fails when a care-of address is changed by a Binding Update Message with a malicious intent. When this failure occurs, a packet arrives at an undesired destination instead of arriving at a proper destination. It is thus preferable, from the standpoint of security, that only those Binding Update Messages from a trusted home agent 13 be used. Accordingly, the foreign agent (32, 52, 62) according to the sixth embodiment accepts only those Binding Update Messages from the selected home agents 13.

30 The foreign agent (32, 52, 62) according

09865694-052901  
T06250-4695860

to the sixth embodiment is provided with an internal table in which the selected home agents 13 are registered. The foreign agent (32, 52, 62) updates the care-of address of the mobile terminal 11 only in accordance with the Binding Update Messages from the home agents 13 positively registered in the internal table. Binding Update Messages from the other home agents 13 are ignored.

Fig. 16 is an example of an internal table in which the selected home agents 13 are specified. As shown in Fig. 16, each of the IP addresses of the home agents 13 listed is mapped into information indicating whether the Binding Update Message from the corresponding home agent is acceptable. In the case of the internal table of Fig. 16, the Binding Update Message from the home agent 13 having the IP address 10.76.51.254 is accepted. The Binding Update Message from the other home agents 13 is not accepted.

The other aspects of the operation according to the sixth embodiment are the same as the corresponding aspects according to the third embodiment so that the description thereof is omitted.

As described, according to the sixth embodiment, only those Binding Update Message from the selected home agents 13 are accepted. Thus, it is ensured that only those Binding Update Messages from the trusted home agents 13 are used, resulting in reinforcement of the security.

09065694-052901

### Seventh embodiment

In a seventh embodiment, the home agents 13 registered in the internal table provided in the foreign agent (32, 52, 62) according to the sixth embodiment are arranged into groups, using a subnet mask.

Fig. 17 shows an example of an internal table in which grouping using a subnet mask is introduced. In the case of the internal table shown in Fig. 17, only those Binding Update Messages from the home agents 13 belonging to the subnet having the IP address 10.76.0.0 are accepted with an exception of the home agent 13 having the IP address 10.76.55.254.

Thus, according to the seventh embodiment, the home agents 13 whose Binding Update Message is accepted are listed using subnet grouping. With this, identification the selected home agents 13 assigned the authority to issue an acceptable Binding Update Message is easily implemented.

### Eighth embodiment

The foreign agent (32 52, 62) according to an eighth embodiment encapsulates only those IP packets from selected correspondent terminals (41-1, 41-2) and tunnels the encapsulated packets.

The foreign agent (32, 52, 62) according to the eighth embodiment is provided with a service

setting table in which information indicating whether Route Optimization is executed for the correspondent terminal 41-i (i=1, 2) located in the home IP network (3, 5, 6).

5                    Fig. 18 shows an example of a service setting table. When the service setting table shown in Fig. 18 is provided in the network shown in Fig. 10, the foreign agent 52 (32, 42) encapsulates IP packets from the correspondent terminal 41-1 having  
10 the home address 10.76.55.100 and tunnels the encapsulated packets. In contrast, the foreign agent 52 forwards IP packets from the correspondent terminal 41-2 having the home address 10.75.55.101 transparently.

15                    A description will now be given of the operation according to the eighth embodiment.

Fig. 19 is an SDL diagram showing the operation of the foreign agent (32, 52, 62) according to the eighth embodiment.

20                    Referring to the network shown in Fig. 10, the when the foreign agent (32, 52, 62) according to the eighth embodiment receives an OP packet in step ST21 via the Internet 2 or a correspondent terminal in the home IP network (3, 5,  
25 6), the foreign agent (32, 52, 62) examines the IP packet so as to determine whether the IP packet is destined for an address in the home IP network (3, 5, 6). When it is determined that the IP packet is destined for an IP address in the home IP network  
30 (3, 5, 6), the foreign agent (32, 52, 62)

5                   When it is determined that the received  
IP packet is not destined for an IP address in the  
home IP network (3, 5, 6), the foreign agent (32,  
52, 62) refers to the service setting table in step  
ST121 so as to determine in step ST122 whether the  
0 packet is to be processed with Route Optimization.

When it is determined that the packet is  
not to be processed with Route Optimization as a  
result of referring to the service setting table,  
or when it is determined that the destination  
mobile terminal is not registered in the binding  
cache table, the foreign agent (32, 52, 62)  
forwards the IP packet transparently in step ST126.



The other aspects of the eighth embodiment are the same as the corresponding aspects according to the first embodiment so that the description thereof is omitted.

5           As described, according to the eighth embodiment, the foreign agent (32, 52, 62) is configured to encapsulate only those IP packets from selected correspondent terminals. A network manager is thus capable of individually specifying  
10 whether to execute Route Optimization. Data tolerant of delay, i.e. data not requiring real-time processing, may be processed without Route Optimization while data not tolerant of delay (such as VoIP data) are processed with Route Optimization,  
15 thus reducing the load imposed on the foreign agent (32, 52, 62).

#### Ninth embodiment

          The foreign agent (32, 52, 62) according  
20 to a ninth embodiment introduces a subnet mask in the service setting table. The need for Route Optimization is inclusively specified for a group of correspondent terminals 41-i belonging to a subnet.

25           Fig. 20 shows an example of a service setting table in which a subnet mask is introduced. The service setting table shown in Fig. 20 establishes that only those IP packets from the correspondent terminals belonging to the subnet  
30 10.76.55.0 are processed with Route Optimization

09865694 052901  
T06250 16959867

with the exception of the correspondent terminal having the IP address 10.75.55.101.

The other aspects of the operation are the same as the corresponding aspects according to the eighth embodiment so that the description thereof is omitted.

As described, according to the ninth embodiment, a subnet mask is used to inclusively specify the need for Route Optimization for a group of correspondent terminals belonging to the subnet. An advantage arising from this arrangement is that the service setting table is generated efficiently.

#### Tenth embodiment

The foreign agent (32, 52, 62) according to a tenth embodiment adjusts the interval of transmission of a Binding Request Message in accordance with the frequency of change of the care-of address of the mobile terminal.

A description will now be given of the operation according to the tenth embodiment.

Fig. 21 is an SDL diagram showing the operation of the foreign agent (32, 52, 62) adjusting the interval of transmission of a Binding Request Message. Fig. 22 shows a binding cache table provided in the foreign agent (32, 52, 62) according to the tenth embodiment.

When the foreign agent (32, 52, 62) receives a Binding Update Message in step ST141, the foreign agent (32, 52, 62) searches the binding

105250-16959550

In step ST143, the foreign agent (32, 52,

As shown in Fig. 22, the frequency of change of the care-of address and the priority of update are registered against each of the mobile terminal.

30           When it is determined that the mobile

terminal is registered in the binding cache table and that the care-of address included in the Binding Update Message is the same as the care-of address in the binding cache table, the process is  
5 terminated since there is no need to change the care-of address.

In step ST131, when an internal timer of the foreign agent (32, 52, 62) gives a notice of timeout indicating that it is time to transmit a  
10 Binding Request Message, the foreign agent (32, 52, 62) searches the binding cache table for the care-of address corresponding to the timer in step ST132. In step ST133, the foreign agent (32, 52, 62) transmits a Binding Request Message. In step ST134,  
15 the foreign agent (32, 52, 62) resets the frequency of change of the care-of address to 0 and computes a timer value in accordance with the priority of update. In step ST135, the foreign agent (32, 52, 62) starts the timer in order to remind itself of  
20 the occasion to transmit the next Binding Request Message.

The other aspects of the operation according to the tenth embodiment are the same as the corresponding aspects according to the first  
25 embodiment so that the description thereof is omitted.

As described, according to the tenth embodiment, the foreign agent (32, 52, 62) adjusts the interval of transmission of a Binding Request  
30 Message in accordance with the frequency of change

09065694-052904

5

### Eleventh embodiment

10

15

A description will now be given of the operation according to the eleventh embodiment.

25

30

agent (32, 52, 62) then starts a timer for timing the transmission of next Binding Request Message to the mobile terminal 11-i.

The other aspects of the operation according to the eleventh embodiment are the same as the corresponding aspects according to the tenth embodiment so that the description thereof is omitted.

When the initial values of priority of  
10 update are set as shown in Fig. 23, the Binding  
Request Message for the mobile terminal 11-1 having  
the IP address 10.76.51.100 is transmitted more  
frequently than the Binding Request Message for the  
mobile terminal 11-2 having the IP address  
15 10.76.51.101, given that the lifetime of the  
Binding Update Message is unchanged.

As described, according to the eleventh embodiment, the foreign agent (32, 52, 62) sets the initial value of priority of update for each mobile terminal 11-i. With this, it is ensured that the varying quality of Route Optimization service is provided for a plurality of mobile terminals 11-i.

## Twelfth embodiment

25           The foreign agent (32, 52, 62) according  
to a twelfth embodiment registers a plurality of  
care-of addresses for a mobile terminal in a  
binding cache table so that IP packets destined for  
the home address of the mobile terminal are  
30 tunneled to each of the plurality of care-of

addresses.

When the mobile terminal is located at a boundary between a plurality of IP networks, handover may take place frequently. In this situation, the mobile terminal frequently notifies the home agent 13 of a change in the care-of address, increasing the network load and power consumption of the mobile terminal. The Mobile IP protocol allows the mobile terminal at a boundary between a plurality of IP networks to register a plurality of care-of addresses in order to eliminate the necessity for the mobile terminal to frequently change the care-of address. In triangular routing, the home agent 13 in which the plurality of care-of addresses are registered forwards the IP packets destined for the mobile terminal to each of the plurality of care-of addresses.

However, since IP packets destined for the mobile terminal are not routed via the home agent according to the related-art Route Optimization, IP packets are forwarded to only one of the plurality of care-of addresses.

The foreign agent (32, 52, 62) according to the twelfth embodiment registers, in the binding cache table, the plurality of care-of addresses registered in the home agent 13 so that the routes to the care-of addresses are optimized.

A description will now be given of the operation according to the twelfth embodiment.

0985694-052901  
TOPSECRET

Fig. 24 shows an example of an extended Binding Update Message according to the twelfth embodiment.

When the home agent 13 in which a plurality of care-of addresses are registered for a given mobile terminal 11 receives a Binding Request Message for the mobile terminal 11, the home agent 13 sends an extended Binding Update Message as shown in Fig. 24 to the foreign agent (32, 52, 62) originating the Binding Request Message. The extended portion of the Binding Update Message contains second and subsequent care-of addresses.

The foreign agent (32, 52, 62) receiving the extended Binding Update Message reads a first care-of address from the unextended portion and reads additional care-of addresses from the extended portion. The foreign agent (32, 52, 62) then registers the care-of addresses thus read in the binding cache table in relation to the target mobile terminal 11.

The foreign agent (32, 52, 62) receiving an IP packet destined for the home address of the mobile terminal 11 tunnels the IP packet to each of the plurality of care-of addresses corresponding to the home address.

The other aspects of the twelfth embodiment are the same as the corresponding aspects of the first embodiment so that the description thereof is omitted.

As described, according to the twelfth



registers a plurality of care-of addresses for the mobile terminal 11 in the binding cache table, as the situation demands. IP packets destined for the

Accordingly, even when the care-of address of the mobile terminal 11 located at a boundary between network domains changes frequently, it is ensured

### Thirteenth embodiment

When a correspondent terminal visits an IP network (3, 5, 6), the foreign agent (32, 52, 62) according to a thirteenth embodiment acquires information registered in a binding cache table provided in the remote foreign agent (32, 52, 62) belonging to the remote IP network (3, 5, 6) from which the visiting correspondent terminal arrived. The information thus acquired is registered in the binding cache table of the acquiring foreign agent (32, 52, 62).

In the related-art Route Optimization, when a correspondent terminal originating an IP packet moves across IP networks, IP packets from the correspondent terminal to a target mobile terminal are temporarily routed via the home agent

of the target mobile terminal until the foreign agent of the visited IP network receives a Binding Update Message, since the foreign agent does not have information relating to the correspondent terminal registered in the binding cache table. Consequently, the same operation performed according to a sequence of Fig. 9 when the correspondent terminal transmits an IP packet for the first time is repeated whenever the correspondent terminal moves across IP networks. Thus, triangular routing occurs temporarily.

The foreign agent (32, 52, 62) according to the thirteenth embodiment resolves the problem of temporary triangular routing occurring when the correspondent terminal moves across IP networks, by allowing the foreign agent (32, 52, 62) of the visited IP network to acquire registered information from the binding cache table of the remote foreign agent (32, 52, 62) of the remote IP network from which the visiting correspondent terminal arrived.

A description will now be given of the operation according to the thirteenth embodiment.

Fig. 25 shows that the correspondent terminal 41 of the network shown in Fig. 1 moves to the remote IP network 6. Figs. 26 and 27 are SDL diagrams showing the operation of the foreign agent (32, 52, 62) according to the thirteenth embodiment.

When the foreign agent 62 (32, 52) according to the thirteenth embodiment receives a

Registration Request Message in step ST11, control is successively turned to steps ST12, ST13, ST14 and ST15. In step ST151, a determination is made as to whether the Registration Request Message contains an extended portion (described later). If it is determined that the Registration Request Message contains an extended portion, control is turned to step ST152, where the foreign agent 62 (32, 52) sends a Binding Update Message informing a foreign agent 52 (32, 62), to which the visiting correspondent terminal 41, of the care-of address of the visiting correspondent terminal 41 originating the Registration Request Message. Subsequently, in step ST16, the foreign agent (32, 52, 62) forwards the Registration Request Message to the home agent 43 for the correspondent terminal 41 originating the Registration Request Message (or the home agent 13 for the mobile terminal).

When the foreign agent (32, 52, 62) according to the thirteenth embodiment receives an IP packet in step ST21 and when it is determined in step ST22 that the IP packet is destined for an IP address in the home IP network (3, 5, 6), the foreign agent decapsulates the IP packet.

In step ST161, the foreign agent (32, 52, 62) searches the attached terminal management table for a terminal having the home address identical to the destination address of the IP packet. In step ST162, a determination is made as to whether there is such a terminal. If it is determined that there

09865694-052904  
T06250-4699860

```
5 IP packet is delivered to that terminal.
```

If it is determined that the attached terminal management table does not list a terminal having the home address identical to the destination address of the IP packet, it is determined that the destination terminal is not located in the home IP network (3, 5, 6) of the foreign agent (32, 52, 62). In a subsequent step ST163, the foreign agent (32, 52, 62) then searches the binding cache table so as to determine in step ST164 whether the packet destination terminal (mobile terminal 11) is registered in the binding cache table. If it is determined that the mobile terminal 11 to which the IP packet is addressed is registered in the binding cache table, the foreign agent (32, 52, 62) decapsulates the IP packet in step ST165. In step ST166, the foreign agent (32, 52, 62) forwards the encapsulated IP packet to the current care-of address of the mobile terminal 11. In step ST167, an alarm is given indicating that the destination mobile terminal 11 is not attached to the IP network, (3, 5, 6) of the foreign agent (32, 52, 62). If it is determined that the destination mobile terminal 11 is not registered in the binding cache table, the foreign agent (32, 52, 62) discards the IP packet.

When the foreign agent (32, 52, 62) receives a Binding Update Message in step ST131, control is successively turned to steps ST33, ST34 or ST35. In a subsequent step ST171, a

5 determination is made as to whether the Binding Update Message is from another foreign agent (32, 52, 62). If it is determined that the Binding Update Message is from another foreign agent (32, 52, 62), a Binding Acknowledge Message containing  
10 the contents of the local binding cache table is sent to the foreign agent (32, 52, 62) originating the Binding Update Message in step ST172.

When the foreign agent (32, 52, 62) receives the Binding Acknowledge Message in step  
15 ST181, the foreign agent (32, 52, 62) generates, in step ST182, a binding cache table based on the contents of the Binding Acknowledge Message or appends the contents to the existing cache table.

A description will now be given of the  
20 operation performed by terminals and agents when the correspondent terminal 41 moves from the IP network 5 to the IP network 6. Fig. 28 shows a sequence of operations performed by terminals and agents when the correspondent terminal 41 moves to  
25 a remote IP network 6. The base station (12, 31, 42, 51, 61) merely performs transparent transmission so that the description of the operation thereof is omitted.

As shown in Fig. 25, upon moving from  
30 the IP network 5 to the IP network 6, the

09865694-052901  
T.06250-46959860

correspondent terminal 41 acquires a care-of address via, for example, an agent advertisement from the foreign agent 62.

5       The correspondent terminal 41 acquiring the care-of address notifies the home gent 43 of the care-of address thus acquired and sends a Registration Request Message to the foreign agent 62 of the IP network 6 to which the correspondent terminal 41 currently belongs.

10       The Registration Request Message is an extended version including an instruction for causing the foreign agent 62 to notify the foreign agent 52 of the care-of address of the correspondent terminal. This extension is in  
15       accordance with the IETF Internet draft (draft-ietf.mobileip-optim-08.txt). The extended Registration Request Message includes the old care-of address and the new care-of address of the correspondent terminal 41.

20       When receiving the Registration Request Message 6, the foreign agent 62 generates a Binding Update Message for notifying the foreign agent 52 of the care-of address of the correspondent terminal 41 and sends the generated message to the  
25       foreign agent 52.

30       The foreign agent 52 receiving the Binding Update Message generates a binding cache table in which the old care-of address of the correspondent terminal 41 is mapped into the new care-of address. The foreign agent 52 also sends a

0065594-46959860

5

10

20

30

according to the thirteenth embodiment are the same as the corresponding aspects according to the first embodiment so that the description thereof is omitted.

5                   As described, according to the  
thirteenth embodiment, when the correspondent  
terminal 41 moves across IP networks, the foreign  
agent (32, 52, 62) of the destination IP network (3,  
5, 6) acquires the information registered in the  
10 binding cache table provided in the foreign agent  
(32, 52, 62) of the source IP network (3, 5, 6) so  
as to register the acquired information in the  
local binding cache table. With this, a temporary  
triangular routing is prevented from occurring so  
15 that Route Optimization is properly maintained.

#### Fourteenth embodiment

                  The foreign agent (32, 52, 62) according  
to the fourteenth embodiment monitors the volume of  
20 IP packets exchanged between the correspondent  
terminal 41 belonging to the home IP network (3, 5,  
6) and the mobile terminal 11. Depending on the  
volume monitored, the foreign agent (32, 52, 62)  
refrains from updating the care-of address  
25 registered in the binding cache table.

                  In accordance with the first through  
thirteenth embodiments described above, the foreign  
agent (32, 52, 62) periodically updates the care-of  
address of the mobile terminal 11 once it is  
30 registered in the binding cache table. An update

0985564-05901  
T06250-1695960



occurs even when the correspondent terminal 41 has not transmitted any IP packets. As a result, the care-of address of the mobile terminal 11 less frequently receiving an IP packet is also  
5 periodically updated.

The foreign agent (32, 52, 62) according to the fourth embodiment refrains from updating the care-of address of the mobile terminal 11 less likely to receive an IP packet.

10 A description will now be given of the operation according to the fourteenth embodiment.

The foreign agent (32, 52, 62) of the IP network (3, 5, 6) to which the correspondent terminal 41 currently belongs reads a destination  
15 IP address and an origination IP address specified in a received packet so as to compute a volume of traffic between the mobile terminal 11 and the correspondent terminal 41.

When the traffic of IP packets between  
20 the mobile terminal 11 and the correspondent terminal 41 is absent for a predetermined period of time, the foreign agent (32, 52, 62) suspends the transmission of a Binding Request Message and update of care-of address in the binding cache  
25 table.

The other aspects of the operation, according to the fourteenth embodiment are the same as the corresponding aspects according to the first embodiment so that the description thereof is  
30 omitted.

09865694-052901

As described, according to the  
fourteenth embodiment, the foreign agent (32, 52,  
62) monitors the volume of traffic of IP packets  
from the mobile terminal 11 and IP packets destined  
5 for the mobile terminal 11. The foreign agent (32,  
52, 62) refrains from updating the care-of address  
of the mobile terminal 11 in the binding cache  
table depending on the monitored volume.  
Accordingly, the volume of packets for exchanging  
10 messages between the foreign agent (32, 52, 62) and  
the home agent 13 is reduced.

#### Fifteenth embodiment

The foreign agent (32, 52, 62) according  
15 to the fifteen embodiment suspends the update of  
care-of address registered in the binding cache  
table when the correspondent terminal 41 moves out  
of the local IP network (3, 5, 6).

A description will now be given of the  
20 operation according to the fifteenth embodiment.

Referring to the network of Fig. 25,  
when the correspondent terminal 41 moved from the  
IP network 5 accommodating the foreign agent 52 to  
the IP network 6 accommodating the foreign agent 62,  
25 a Binding Update Message is transmitted from the  
foreign agent 62 to the foreign agent 52, as shown  
in Fig. 28.

With this, the foreign agent 52 is  
informed that the correspondent terminal 41 has  
30 left the IP network 5. Even when the Binding Update

5 is no longer valid.

10 the mobile terminal 11. Therefore, the foreign

20 table. Accordingly, the volume of packets for

## Sixteenth embodiment

25           The foreign agent (32, 52, 62) according  
to the sixteenth embodiment resumes the update of  
care-of address when a certain condition is met.

A description will now be given of the operation according to the sixteenth embodiment.

30           The foreign agent (32, 52, 62) resumes

the update of care-of address when it receives a Binding Update Message for the care-of address for which the update was suspended in accordance with the fourteenth and fifteenth embodiments.

- 5 Alternatively, the update of care-of address may be resumed when tunneling transmission to the care-of address occurs.

Thus, according to the sixteenth embodiment, the update of care-of address is  
10 resumed when a certain condition is met. Accordingly, the update of care-of address is performed at an appropriate frequency adapted for the purpose. With this, the volume of packets for exchanging messages between the foreign agent (32,  
15 52, 62) and the home agent 13 is reduced.

In the description given above, the function of the foreign agent (32, 52, 62) and the function of the home agent (13, 43) are assumed to be separate from each other. Alternatively, the  
20 home agent (13, 43) may be provided with the function of a foreign agent for terminals not belonging to the home agent (13, 43).

The present invention is not limited to the above-described embodiments, and variations and  
25 modifications may be made without departing from the scope of the present invention.

09865694 052901  
"106250" 46959860